


FS Casale

Porcelain tiles



FS CASALE



10 patterns

45,2 * 45,2 * 1 cm | 16^{5/8} * 16^{5/8} * 3/8"

NO RECTIFIED	NATURAL PRICE CODE BN61
FS CASALE	21077

CARACTERÍSTICAS TÉCNICAS ANTIDESLIZAMIENTO | ANTI-SLIP CHARACTERISTICS

Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R10
DIN 51097	Ángulo crítico (Pies descalzos) Critical angle (Wet loaded barefoot)	-
BS-7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	+36Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 2
ANSI A.1371:2012	Coefficiente de Fricción Dinámico Dynamic Coefficient of Friction	> 0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	PEI 4

APLICACIONES | APPLICATIONS

Área Area	Revestimiento Wall	Pavimento Floor
Interior Internal	✓	✓
Exterior External	✓	✓
Comercial Commercial	✓	✓
Ducha Shower	✓	-

CARACTERÍSTICAS TÉCNICAS | TECHNICAL CHARACTERISTICS

joint	versatile	matt
1,5 mm		
diferent shades	shade variation	various graphics
	v3	

EMBALAJE | PACKING

Formato Sizes	Cajas Boxes			Pallet			Cont./20' 21500 kg.	Cont./20' 24000 kg.	
	Piezas	m ² / sq.m	kg	Cajas	m ² / sq.m	kg			Tamaño cm aprox.
cm									
45,2 * 45,2 * 1	5	1,02	23,70	66	67,42	1589,20	120 * 80 * 105	912,12	1018,18
inch	Units	ft ²	lb	Boxes	ft ²	lb	Sizes inch approx.	ft ²	ft ²
16 ^{5/8} * 16 ^{5/8} * 3/8	5	11,00	52,14	66	725,71	3496,24	47 ^{1/4} * 31 ^{1/2} * 41 ^{5/16}	9817,94	10959,56