


OPAL

20x20 cm



Opal white 20x20 cm



wall: Opal black _ white_silver_gold 20x20 cm floor: Branch maple natural 24,9x100 cm

OPAL

20x20 cm - 7.9"x7.9"

Wall Tiles
Revestimiento

Double firing
Bicocción



Opal White*
20 x 20 cm C-430



Opal Black*
20 x 20 cm C-430




Opal Silver*
20 x 20 cm C-320




Opal Gold*
20 x 20 cm C-320



Opal Bronze*
20 x 20 cm C-320



Pop White
20 x 20 cm C-410



Pop White Corner
2 x 20 cm C-130



Pop Black
20 x 20 cm C-430




Pop Black Corner
2 x 20 cm C-130

*Relief with a fixed position when tiling.
Relieve con posición en la colocación.


Physical Vapor Deposition (PVD)
Pvd is a field in the application of nanotechnology. The process consists of depositing layers of atoms, inside a vacuum chamber, to a solid surface. The layering is produced by the condensation of a vaporized metal (such as gold, titanium, platinum etc.) over the selected surface.
Advantages: High resistance to abrasion and scratches; much higher than metals applied by firing.
Corrosion resistant. ISO 9227
As a general rule, any non-aggressive, pH neutral product have to be used.
Do not mix pieces from different lots.

El PVD es uno de los campos de aplicación de la nanotecnología. El proceso consiste en depositar capas de átomos, en una cámara de alto vacío, sobre una superficie sólida. El recubrimiento se produce por la condensación de un metal vaporizado, oro, titanio, platino, ect. sobre el material a recubrir.
Ventajas: Mayor resistencia al rayado y a la abrasión que los metales aplicados por cocción.
Resistente a la corrosión : ISO 9227
Para la limpieza de estos materiales deben utilizarse productos no agresivos con pH neutro.
No mezclar piezas de diferentes lotes.

Matching floor tiles / Pavimento coordinado




Primary White Natural
29,5 x 29,5 cm G-3142



Primary Black Natural
29,5 x 29,5 cm G-3142



Sincro Blanco
31,6 x 31,6 cm C-870



Sincro Negro
31,6 x 31,6 cm C-880

* Matching floor tiles. We recommend to lay this product with a 2 mm grout.
Pavimento de igualación. Se recomienda colocar este producto con una junta de separación de 2 mm.

Series	Format&Thickness	Unit	Boxes/Pallet	m²/Pallet	m²/Box	Pieces/Box	Kg/Pallet	Kg/Box
Opal White / Black	20x20	m²	100	88,00	0,88	22	1128,2	11,14
Opal Gold/Silver/Bronze	20x20	PZ	75	54,00	0,72	18	700,47	9,15
Pop / Art	20x20	m²	100	100,00	1,00	25	1278,5	12,65
Pop Corner	2x20	pz	48	10,37	1,00	54	182,48	3,51
Primary Natural	29,5x29,5	m²	72	50,112	0,969	8	1123,88	15,42
Sincro	31,6x31,6	m²	62	62,00	1,00	10	1134,00	15,42

